



Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A

This specification is referred to the 1.20mm series wire to board connector

索引【INDEX】

1. 适用范围【Scope】
2. 规格与料号【Spec and Part number】
3. 材质与表面处理【Disposal of Material and surface】
4. 额定等级【Ratings and applicable wires】
5. 性能【Performance】
 - 5-1. 电气的性能【Electrical Performance.】
 - 5-2. 机械的性能【Mechanical Performance】
 - 5-3. 环境性能及其它【Environmental Performance and Others】
6. 综合插入力及拔出力【Insertion/Withdrawal Force】
7. SMT 回流条件【SMT Reflow Condition】



Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A

【1.适用范围 Scope】

此种规格包括 1.20mm Pitch 1224 Series 连接器规格说明。

This Specification Covers the 1.20mm Pitch 1224 Series Connector Specification.

【2.规格与料号 Spec and Part number】

规格内容 Specification	产品料号 Production No.	产品图示 Picture of Product
端子/Terminal	1224T-XV01	
胶壳/Housing	1224H-XXX-LP	
针座/Wafer	1224WRS-XXX-XXV01	

【3.材质与表面处理 Disposal of Material and surface】

规格内容 Specification	材质 Materials	表面处理 Disposal of Surface
端子/Terminal	磷铜(C5191)/Phosphor Bronze	Nickel: Over 30μ". Gold Flash
胶壳/Housing	LCP	UL 94V-0
针座/Wafer	Base	PA4T
	PIN	磷铜(C5191)/Phosphor Bronze
	Solder tab	磷铜(C5191)/Phosphor Bronze
		Over Tin 70 μ" Plated Over 30 μ" Nickel

(上述参数请以工程图为准/Please Refer to the Project drawing for the above Specification)

【4. 额定等级 Ratings and applicable wires】

项目【Item】	规格【Standard】	
额定电压 Rated Voltage (Max.)	50V	[AC/DC]
额定电流 Rated Current (Max.)	2A	
使用温度范围 Ambient temperature Range	-25°C~+85°C	
适用线径 Applicable wire insulation O.D	28 AWG~30 AWG(0.08~0.05 mm ²) Insulation O.D. 0.70mm(Max.)	

【*升温时含端子.Including terminal temperature rise.



Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A

【5.性能 PERFORMANCE】

5-1. 电气的性能 Electrical Performance.

项目 【Item】	条件 【Test Condition】	规格 【Requirement】
5-1-1 接触阻抗 Contact Resistance	<p>公母配合,开放电压 20mV 以下,电流 10mA 检测连接器 A~B 区. Mate connectors, measure by dry circuit, 20mV MAX, 10mA. (Based upon EIA-364-06A).</p>	<p>Initial: 20 milliohms Max. After Test: 40 milliohms Max.</p>
5-1-2 绝缘阻抗 Insulation Resistance	<p>公母配合,在相邻端子,端子与地片之间,使用 500V 的直流电,检测连接器. Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond.B)</p>	100 Megohms Min.
5-1-3 耐电压 Dielectric Strength	<p>公母配合,在相邻端子,端子与地片之间,使用 500V 的交流电 1 分钟,检测连接器. Mate connectors, apply 500V AC for 1 minute between adjacent terminal or ground. (Based upon EIA-364-20A / MIL-STD-202 Method 301)</p>	不出现中断等情况 No Breakdown and Flashover
5-1-4 铆线后端子接触阻抗 Contact resistance on crimped portion	<p>铆线后之端子,开放电压 20mV 以下,电流 10mA 检测连接器. Crimp the applicable wire on to the terminal measure by dry circuit 20mV MAX, 10mA.</p>	10 milliohms Max.




Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A

5-2. 机械的性能 Mechanical Performance.

项目 【Item】	条件 【Test Condition】	规格 【Requirement】
5-2-1 插拔力 Insertion & withdraw Force	<p>以每分钟 25.4±3mm 的速率插入和拔出。 Insert and withdraw Connectors at the speed rate of 25.4±3mm/minute.</p>	参照第 6 项 Refer to paragraph 6
5-2-2 端子保持力 Terminal/ Housing Retention Force	<p>以每分 25.4±3mm 的速率,将端子从 Housing 内轴向拔出的力量。 Apply axial pull out force at the speed rate of 25.4±3mm/minute on the terminal assembled in the housing.</p>	3.92N {0.4kgf} Min.
5-2-3 端子插入力 Terminal Insertion Force	<p>铆线后之端子插入 Housing 所需最大力量。 Insert the crimped terminal into the housing.</p>	9.8N {1.0kgf} Max.
5-2-4 Pin 针保持力 Pin Retention Force	<p>以每分 25.4±3mm 的速率,将 PIN 针从 Wafer 内轴向推出的力量。 Apply axial push force at the speed rate of 25.4±3mm/minute.</p>	0.5N {0.05kgf} Min.
5-2-5 固定片保持力 Fixture Retention Force	<p>以每分 25.4±3mm 的速率,将 PIN 针从 Wafer 内轴向推出的力量。 Apply axial push force at the speed rate of 25.4±3mm/minute.</p>	0.98N {0.1kgf} Min.



Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A

项目 【Item】	条件 【Test Condition】	规格 【Requirement】		
5-2-6 端子压着强度 (Crimped contact)	固定铆线后的端子, 使电线与端子分离时所需的最小力量。 Fix the crimped terminal, apply axial pull out force on the wire. (Do not crimp insulation part). 	AWG	28	30
		Spec.kgf. Min.	1.0	0.5
		Note> As for unspecified wire sizes in this specification define values with clients		

5-3. 环境性能及其它 Environmental Performance and Others.

项目 【Item】	条件 【Test Condition】	规格 【Requirement】	
5-3-1 重复插拔 Repeated Insertion/ Withdrawal	以每分钟不超过 10 次的速率, 将公母插拔 10 次。 When mated up to 10 cycles repeatedly by the rate of 10 cycles per minute.	接触阻抗 Contact Resistance	40 milliohms Max.
5-3-2 温升测试 Temperature Rise	温升测试: 公母连接器配合后, 加载额定电流直到温度上升到稳定状态, 然后再测量温升 (EIA364-70, Method 1) Mating connectors shall be energized at rating current until thermal stability is achieved, and then measured the temperature rise. (EIA364-70, Method 1)	温升测试 Temperature rise	30°C Max.
5-3-3 振动测试 Vibration test	振幅: 1.5mm P-P 时间: 20~200~20 Hz in 3minute 持续时间: 每轴向 3 小时 加速度: 44m/S ² 开放电压: 20mV 以下 开放电流: 10mA 以下 Amplitude: 1.5mm P-P Sweep time: 20~200~20 Hz in 3 minute Duration: 3 hours in each X.Y.Z axials. (Based upon EIA-364-28B/MIL-STD-202 Method 213B Cond.A)	外观 Appearance	无异状 No Damage
		接触阻抗 Contact Resistance	40 milliohms Max.
		瞬断 Discontinuity	1 micro-second Max.
5-3-4 冲击测试 Shock test	在 X.Y.Z 上 6 个方向上, 以 981m/s ² (100G 的力量)冲击下各 3 回. 作用时间: 6ms 981m/s ² {100G}, 3 strokes in each X.Y.Z. axes. Operation time:6ms (Based upon EIA-364-27B/MIL-STD-202 Method 213B Cond. A)	外观 Appearance	无异状 No Damage
		接触阻抗 Contact Resistance	40 milliohms Max.
		瞬断 Discontinuity	1 micro-second Max.



Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A

项目 【Item】		条件 【Test Condition】	规格 【Requirement】	
5-3-5	耐热性 Heat Resistance	85±2℃, 96 hours. (Based upon MIL-STD-202 Method 108A Cond.A)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
5-3-6	耐寒性 Cold Resistance	-25±5℃, 96 hours. (Based upon EIA-364-105)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
5-3-7	耐湿性 Humidity	温度: 40±2℃ 湿度: 90~95%(RH) 持续时间: 96 hours Temperature: 40±2℃ Relative Humidity: 90~95% Duration: 96 hours (Based upon EIA-364-31A/MIL-STD-202 Method 103B Cond.B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
			耐电压 Dielectric Strength	Must meet 5-1-3
			绝缘阻抗 Insulation Resistance	100 Megohms Min.
5-3-8	温度变化 Temperature Cycling	从-25℃持续 30 分钟升至+85℃持续 30 分钟,循环 5 次. 5 cycles of: a) -25℃ 30 minutes. b) +85℃ 30 minutes. (Based upon EIA-364-32B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
5-3-9	盐水喷雾 Salt Spray	在温度 35±2℃, 盐水浓度 5±1% 下, 盐水喷雾 24±1 小时. 24±1 hours exposure to a salt spray from the 5±1% solution at 35±2℃. (Based upon EIA-364-26B/MIL-STD-202 Method 101D Cond.B).	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	40 milliohms Max.
5-3-10	焊锡附着性 Solder-ability	焊接时间: 3~5 秒. 焊接温度: 245±5℃. Soldering Time: 3~5 sec solder Solder Temperature: 245±5℃. (Based upon EIA-364-52)	Solder Wetting	浸渍面积需 95% 以上 95% of immersed area must show no voids, pin holes.



Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A


项目 【Item】	条件 【Test Condition】	规格 【Requirement】	
5-3-11 焊锡耐热性 Solder- Resistance	焊接时间: 5~10 秒. 焊接温度: 255+5/-5°C. Soldering time: 5~10 sec solder. Temperature: 255+5/-5°C. (Based upon EIA-364-56A)	外观 Appearance	无异状 No Damage

【6. 综合插入力及拔出力 INSERTION/WITHDRAWAL FORCE】 <Connector mating force>

PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	10 次拔出力(最小值) 10 th Withdrawal (kgf Min.)	PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	10 次拔出力(最小值) 10 th Withdrawal (kgf Min.)
02	1.84	0.12	07	3.30	0.12
03	2.14	0.12	08	3.60	0.12
04	2.45	0.12	09	3.90	0.12
05	2.76	0.12	10	4.20	0.12
06	3.00	0.12			

注: 以上插拔次数为 10 次 Note: Insertion and Withdrawal for 10Cycles

【7. SMT 回流条件 SMT REFLOW CONDITION】



温度条件曲线图/ 基板上温度

TEMPERATURE CONDITION GRAPH/ (TEMPERATURE ON BOARD PATTERN SIDE)

注记: 由于 P.C 板等焊接装置改变条件, 所以请预先用自己的装置检查回流焊的条件。

Notes: Please check the reflow soldering condition by your own devices beforehand. Because the condition changes by the soldering devices, P.C. boards, and so on.



Product Specification [产品规格书]:	Document No	PS-1224-01
Subject [主题]:	Date Issued	2018/1/19
1.20mm Pitch 1224 Series Connector Specification	Date Revised	2018/1/19
	Version	A

8. 测试顺序 QUALIFICATION TEST SEQUENCE

Item 项目	DESCRIPTION 叙述	SEQUENCE 顺序																	METHOD 方法
		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	
1	Examination of product 外观检验	1, 3	1, 4	1	1	1	1	1	1, 4	1, 5	1, 9	1, 9	1, 9	1, 9	1, 5	1, 2	1, 3	1, 3	
2	Contact resistance 接触阻抗									2, 4	2, 8	2, 8	2, 8	2, 8	2, 4				5-1-1
3	Insulation resistance 绝缘阻抗										3, 6	3, 6	3, 6	3, 6					5-1-2
4	Dielectric withstanding Voltage 耐电压										4, 7	4, 7	4, 7	4, 7					5-1-3
5	铆线后端子接触阻抗 Contact resistance on crimped portion																3		5-1-4
6	Mating force 插入力								2										5-2-1
7	Unmating force 拔出力								3										5-2-1
8	端子保持力 Terminal/Housing Retention Force			2															5-2-2
9	端子插入力 Terminal Insertion Force				2														5-2-3
10	Pin 针保持力 Pin Retention Force					2													5-2-4
11	固定片保持力 Fixture Retention Force						2												5-2-5
12	端子压着强度 (Crimped contact)							2											5-2-6
13	重复插拔 Repeated Insertion/ Withdrawal									3									5-3-1
14	TEMPERATURE RISING 温升	2																	5-3-2
15	振动 Vibration		2																5-3-3
16	冲击测试 Shock test		3																5-3-4
17	耐热性 Heat Resistance										5								5-3-5
18	耐寒性 Cold Resistance											5							5-3-6
19	热湿性测试 Humidity												5						5-3-7
20	温度变化 Temperature Cycling													5					5-3-8
21	Salt spray 盐水喷雾														3				5-3-9
22	Solderability 沾锡性																2		5-3-10
23	焊锡耐热性 Solder- Resistance																	2	5-3-11